

**Siemens**  
**EcoTech**



SIMATIC HMI MTP1000, Unified Comfort Panel, touch operation, 10.1" widescreen TFT display, 16 million colors, PROFINET interface, configurable as of WinCC Unified Comfort V16, contains open-source software, which is provided free of charge see enclosed DVD



| General information                                                   |                         |
|-----------------------------------------------------------------------|-------------------------|
| Product type designation                                              | MTP1000 Unified Comfort |
| Display                                                               |                         |
| Design of display                                                     | TFT                     |
| Screen diagonal                                                       | 10.1 in                 |
| Display width                                                         | 217 mm                  |
| Display height                                                        | 135.6 mm                |
| Number of colors                                                      | 16 777 216              |
| Resolution (pixels)                                                   |                         |
| • Horizontal image resolution                                         | 1 280 pixel             |
| • Vertical image resolution                                           | 800 pixel               |
| Backlighting                                                          |                         |
| • MTBF backlighting (at 25 °C)                                        | 50 000 h; At 25°C       |
| • Backlight dimmable                                                  | Yes; 5-100 %            |
| Control elements                                                      |                         |
| Keyboard fonts                                                        |                         |
| • Numeric keyboard                                                    | Yes; Onscreen keyboard  |
| • alphanumeric keyboard                                               | Yes; Onscreen keyboard  |
| Touch operation                                                       |                         |
| • Design as touch screen                                              | Yes                     |
| • Design as multi-touch screen                                        | Yes                     |
| Installation type/mounting                                            |                         |
| Mounting position                                                     | vertical                |
| Mounting in portrait format possible                                  | Yes                     |
| Mounting in landscape format possible                                 | Yes                     |
| maximum permissible angle of inclination without external ventilation | 35°                     |
| Supply voltage                                                        |                         |
| Type of supply voltage                                                | DC                      |
| Rated value (DC)                                                      | 24 V                    |
| permissible range, lower limit (DC)                                   | 19.2 V                  |
| permissible range, upper limit (DC)                                   | 28.8 V                  |
| Input current                                                         |                         |
| Current consumption (rated value)                                     | 0.5 A                   |
| Current consumption, max.                                             | 1.1 A                   |
| Starting current inrush I <sup>2</sup> t                              | 0.5 A <sup>2</sup> s    |
| Memory                                                                |                         |

|                                                          |                                         |
|----------------------------------------------------------|-----------------------------------------|
| Flash                                                    | Yes                                     |
| RAM                                                      | Yes                                     |
| <b>Type of output</b>                                    |                                         |
| Acoustics                                                |                                         |
| • Buzzer                                                 | Yes                                     |
| • Speaker                                                | No                                      |
| <b>Time of day</b>                                       |                                         |
| Clock                                                    |                                         |
| • Hardware clock (real-time)                             | Yes                                     |
| • Software clock                                         | Yes                                     |
| • retentive                                              | Yes; Back-up duration typically 6 weeks |
| • synchronizable                                         | Yes                                     |
| <b>Interfaces</b>                                        |                                         |
| Number of industrial Ethernet interfaces                 | 2; 2 ports (switch) + independent port  |
| Number of RS 485 interfaces                              | 1; RS 422 / 485 combined                |
| Number of RS 422 interfaces                              | 0; together with RS 485                 |
| Number of USB interfaces                                 | 4; USB 3.1 Gen. 1 (type A)              |
| Number of SD card slots                                  | 2                                       |
| Industrial Ethernet                                      |                                         |
| • Industrial Ethernet status LED                         | 2                                       |
| • Number of ports of the integrated switch               | 2                                       |
| <b>Protocols</b>                                         |                                         |
| PROFINET                                                 | Yes                                     |
| Supports protocol for PROFINET IO                        | No                                      |
| Protocols (Ethernet)                                     |                                         |
| • TCP/IP                                                 | Yes                                     |
| • DHCP                                                   | Yes                                     |
| • SNMP                                                   | Yes                                     |
| • DCP                                                    | Yes                                     |
| • LLDP                                                   | Yes                                     |
| Redundancy mode                                          |                                         |
| Media redundancy                                         |                                         |
| — MRP                                                    | Yes                                     |
| <b>EMC</b>                                               |                                         |
| Emission of radio interference acc. to EN 55 011         |                                         |
| • Limit class A, for use in industrial areas             | Yes                                     |
| • Limit class B, for use in residential areas            | No                                      |
| <b>Degree and class of protection</b>                    |                                         |
| IP (at the front)                                        | IP65                                    |
| IP (rear)                                                | IP20                                    |
| NEMA (front)                                             |                                         |
| • Enclosure Type 4x at the front                         | Yes                                     |
| • Enclosure Type 12 at the front                         | Yes                                     |
| <b>Standards, approvals, certificates</b>                |                                         |
| Siemens Eco Profile (SEP)                                | Siemens EcoTech                         |
| CE mark                                                  | Yes                                     |
| UKCA mark                                                | Yes                                     |
| cULus                                                    | Yes                                     |
| RCM (formerly C-TICK)                                    | Yes                                     |
| KC approval                                              | Yes                                     |
| EAC (formerly Gost-R)                                    | Yes                                     |
| CCC                                                      | Yes                                     |
| Ecological footprint                                     |                                         |
| • environmental product declaration                      | Yes                                     |
| Global warming potential                                 |                                         |
| — global warming potential, (total) [CO2 eq]             | 217.7 kg                                |
| — global warming potential, (during production) [CO2 eq] | 54.7 kg                                 |
| — global warming potential, (during operation) [CO2 eq]  | 169 kg                                  |
| — global warming potential, (after end of life cycle)    | -6 kg                                   |

|                                                    |                       |
|----------------------------------------------------|-----------------------|
| [CO2 eq]                                           |                       |
| Use in hazardous areas                             |                       |
| • ATEX Zone 2                                      | Yes                   |
| • ATEX Zone 22                                     | Yes                   |
| • IECEx Zone 2                                     | Yes                   |
| • IECEx Zone 22                                    | Yes                   |
| • cULus Class I Zone 2, Division 2                 | Yes                   |
| • cULus Class II Division 2                        | Yes                   |
| • FM Class I Division 2                            | Yes                   |
| • FM Class II Division 2                           | Yes                   |
| Marine approval                                    |                       |
| • Germanischer Lloyd (GL)                          | No; included in DNV   |
| • American Bureau of Shipping (ABS)                | Yes                   |
| • Bureau Veritas (BV)                              | Yes                   |
| • Det Norske Veritas (DNV)                         | Yes                   |
| • Korean Register of Shipping (KRS)                | Yes                   |
| • Lloyds Register of Shipping (LRS)                | Yes                   |
| • Nippon Kaiji Kyokai (Class NK)                   | Yes                   |
| • Chinese Classification Society (CCS)             | Yes                   |
| Ambient conditions                                 |                       |
| Suited for indoor use                              | Yes                   |
| Suited for outdoor use                             | No                    |
| Ambient temperature during operation               |                       |
| Operation (vertical installation)                  |                       |
| — For vertical installation, min.                  | 0 °C                  |
| — For vertical installation, max.                  | 50 °C                 |
| Operation (max. tilt angle)                        |                       |
| — At maximum tilt angle, min.                      | 0 °C                  |
| — At maximum tilt angle, max.                      | 40 °C                 |
| Operation (vertical installation, portrait format) |                       |
| — For vertical installation, min.                  | 0 °C                  |
| — For vertical installation, max.                  | 40 °C                 |
| Operation (max. tilt angle, portrait format)       |                       |
| — At maximum tilt angle, min.                      | 0 °C                  |
| — At maximum tilt angle, max.                      | 35 °C                 |
| Ambient temperature during storage/transportation  |                       |
| • min.                                             | -20 °C                |
| • max.                                             | 60 °C                 |
| Relative humidity                                  |                       |
| • Operation, max.                                  | 90 %; no condensation |
| Operating systems                                  |                       |
| proprietary                                        | Yes                   |
| configuration / header                             |                       |
| Message indicator                                  | Yes                   |
| Alarm system (incl. buffer and acknowledgment)     | Yes                   |
| Process value display (output)                     | Yes                   |
| Process value default (input) possible             | Yes                   |
| Recipe management                                  | Yes                   |
| Configuration software                             |                       |
| • WinCC Unified Comfort Engineering (TIA Portal)   | Yes                   |
| • WinCC Unified PC Engineering (TIA Portal)        | Yes                   |
| Languages                                          |                       |
| Online languages                                   |                       |
| • Number of online/runtime languages               | 32                    |
| Project languages                                  |                       |
| • Languages per project                            | 32                    |
| Functionality under WinCC Unified                  |                       |
| Libraries                                          | Yes                   |
| Applications/options                               |                       |
| • Writer                                           | Yes                   |

|                                                              |                                  |
|--------------------------------------------------------------|----------------------------------|
| • Web browser                                                | Yes                              |
| • Media Player                                               | Yes                              |
| • SIMATIC WinCC Sm@rtServer                                  | Yes                              |
| • SIMATIC WinCC Audit                                        | Yes                              |
| • Unified Collaboration                                      | Yes                              |
| JavaScript                                                   | Yes                              |
| Task planner                                                 |                                  |
| • time-controlled                                            | Yes                              |
| • task-controlled                                            | Yes                              |
| Help system                                                  |                                  |
| • Number of characters per info text                         | 70                               |
| • Number of message texts per message                        | 10                               |
| functionality under WinCC Unified / alarm system / header    |                                  |
| • Number of alarm classes                                    | 32                               |
| • Bit messages                                               |                                  |
| — Number of bit messages                                     | 9 000                            |
| • Analog messages                                            |                                  |
| — Number of analog messages                                  | 300                              |
| • S7 alarm number procedure                                  | Yes                              |
| • System messages HMI                                        | Yes                              |
| • System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ... ) | Yes                              |
| • Number of characters per message                           | 512                              |
| • Number of process values per message                       | 10                               |
| • Acknowledgment groups                                      | Yes                              |
| • Message indicator                                          | Yes; as dynamic widgets          |
| • Message buffer                                             | Yes; Configured as alarm archive |
| — Circulating buffer                                         | Yes                              |
| — retentive                                                  | Yes                              |
| — maintenance-free                                           | Yes                              |
| Parameter set management (recipes)                           |                                  |
| • Number of parameter set types                              | 750                              |
| • Parameter sets per parameter set type                      | 2 000                            |
| • Entries per parameter set                                  | 1 000                            |
| • Size of internal parameter set memory                      | 12 Mbyte                         |
| • Parameter set memory expandable                            | Yes                              |
| functionality under WinCC Unified / variables / header       |                                  |
| • Number of variables per device                             | 8 000                            |
| • Number of variables per screen                             | 600                              |
| • Limit values                                               | Yes                              |
| • Structures                                                 | Yes                              |
| • Arrays                                                     | Yes                              |
| functionality under WinCC Unified / screens / header         |                                  |
| • Number of configurable images                              | 1 200                            |
| • Faceplate                                                  | Yes                              |
| Image objects                                                |                                  |
| • Number of objects per image                                | 800                              |
| • Picture window                                             | Yes                              |
| • Text fields                                                | Yes                              |
| • I/O fields                                                 | Yes                              |
| • Graphic I/O fields (graphics list)                         | Yes                              |
| • Symbolic I/O fields (text list)                            | Yes                              |
| • Scalable Vector Graphics (SVG)                             | Yes                              |
| • Date/time fields                                           | Yes                              |
| • Checkbox                                                   | Yes                              |
| • Option button                                              | Yes                              |
| • Switches                                                   | Yes                              |
| • Buttons                                                    | Yes                              |
| • Graphic display                                            | Yes                              |
| • Icons                                                      | Yes                              |
| • Custom web display                                         | Yes                              |

|                                                                                |                                          |
|--------------------------------------------------------------------------------|------------------------------------------|
| • Geometric objects                                                            | Yes                                      |
| functionality under WinCC Unified / complex screen objects / header            |                                          |
| • Number of complex objects per screen                                         | 40                                       |
| • Alarm view                                                                   | Yes                                      |
| • Trend view                                                                   | Yes                                      |
| • User view                                                                    | Yes                                      |
| • Status/control                                                               | No                                       |
| • Parameter set display                                                        | Yes                                      |
| • HTML browser                                                                 | Yes                                      |
| • Bar graphs                                                                   | Yes                                      |
| • Sliders                                                                      | Yes                                      |
| • Pointer instruments                                                          | Yes                                      |
| • Analog/digital clock                                                         | Yes                                      |
| functionality under WinCC Unified / lists / header                             |                                          |
| • Number of text lists per project                                             | 750                                      |
| • Number of entries per text list                                              | 750                                      |
| • Number of graphics lists per project                                         | 750                                      |
| • Number of entries per graphics list                                          | 750                                      |
| functionality under WinCC Unified / archiving / header                         |                                          |
| • Number of archives per device                                                | 50                                       |
| • Number of entries per archive                                                | 500 000                                  |
| • Message archive                                                              | Yes                                      |
| • Process value archive                                                        | Yes                                      |
| • type of archiving / for WinCC Unified                                        |                                          |
| — Sequential archive                                                           | Yes                                      |
| — Short-term archive                                                           | Yes                                      |
| • storage location / of archiving / for WinCC Unified                          |                                          |
| — Memory card                                                                  | Yes                                      |
| — USB memory                                                                   | Yes                                      |
| — Ethernet                                                                     | No                                       |
| Security                                                                       |                                          |
| • Number of roles                                                              | 50                                       |
| • Number of function rights                                                    | 20; number of predefined function rights |
| • Number of users                                                              | 200                                      |
| • Password export/import                                                       | Yes                                      |
| • Central user administration                                                  | Yes; as of WinCC V17                     |
| functionality under WinCC Unified / transfer (upload/download) / header        |                                          |
| • USB                                                                          | No                                       |
| • Ethernet                                                                     | Yes                                      |
| • using external storage medium                                                | Yes; as of WinCC Unified V17             |
| Process coupling                                                               |                                          |
| • S7-1200                                                                      | Yes                                      |
| • S7-1500                                                                      | Yes                                      |
| • S7-200                                                                       | No                                       |
| • S7-300/400                                                                   | Yes                                      |
| • Number of S7 connections                                                     | 16                                       |
| • LOGO!                                                                        | Yes; as of WinCC Unified V20             |
| • SIMOTION                                                                     | No                                       |
| • OPC UA Client                                                                | Yes                                      |
| • OPC UA Server                                                                | Yes                                      |
| • Software Controller/Open Controller                                          | Yes                                      |
| functionality under WinCC Unified / service tools/configuration tools / header |                                          |
| • Backup/Restore manually                                                      | Yes                                      |
| • Backup/Restore automatically                                                 | Yes                                      |
| • Simulation                                                                   | Yes                                      |
| • Device switchover                                                            | Yes                                      |
| Peripherals/Options                                                            |                                          |
| Peripherals                                                                    | Printer, barcode reader                  |
| Printer                                                                        | Yes                                      |
| SIMATIC HMI MM memory card: Multi Media Card                                   | No                                       |
| SIMATIC HMI SD memory card: Secure Digital memory card                         | Yes                                      |

|                                               |     |
|-----------------------------------------------|-----|
| SIMATIC HMI CF memory card Compact Flash Card | No  |
| USB memory                                    | Yes |
| SIMATIC IPC USB Flashdrive (USB stick)        | Yes |
| SIMATIC HMI USB stick                         | Yes |
| Network camera                                | No  |

#### Mechanics/material

|                            |     |
|----------------------------|-----|
| Enclosure material (front) |     |
| • Aluminum                 | Yes |

#### Dimensions

|                            |          |
|----------------------------|----------|
| Width of the housing front | 280 mm   |
| Height of housing front    | 205 mm   |
| Mounting cutout, width     | 264.6 mm |
| Mounting cutout, height    | 189.1 mm |
| Overall depth              | 63.6 mm  |

#### Weights

|                            |        |
|----------------------------|--------|
| Weight (without packaging) | 2.1 kg |
|----------------------------|--------|

#### Classifications

|        | Version | Classification |
|--------|---------|----------------|
| eClass | 14      | 27-33-02-01    |
| eClass | 12      | 27-33-02-01    |
| eClass | 9.1     | 27-33-02-01    |
| eClass | 9       | 27-33-02-01    |
| eClass | 8       | 27-24-23-02    |
| eClass | 7.1     | 27-24-23-02    |
| eClass | 6       | 27-24-23-02    |
| ETIM   | 9       | EC001412       |
| ETIM   | 8       | EC001412       |
| ETIM   | 7       | EC001412       |

#### Approvals / Certificates

|                          |     |                                |
|--------------------------|-----|--------------------------------|
| General Product Approval | EMV | For use in hazardous locations |
|--------------------------|-----|--------------------------------|



[KC](#)



|                                |                   |
|--------------------------------|-------------------|
| For use in hazardous locations | Marine / Shipping |
|--------------------------------|-------------------|



[FM](#)

[CCC-Ex](#)



|                   |
|-------------------|
| Marine / Shipping |
|-------------------|



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

|                   |             |
|-------------------|-------------|
| Marine / Shipping | Environment |
|-------------------|-------------|



